

RETAIL PRICE SHEET

July, 2023





WIREWORLD®



CABLE TECHNOLOGY






Engineered
for
Reality™

All prices shown are in U.S. Dollars.
International prices may vary.

Because we are continually striving to improve our products, all specifications and prices are subject to change without notice.










HDMI® CABLES Ethernet / eARC COMPOSILEX 3 insulation	Conductor material Cable design	HDMI Level	0.6m (2 ft.)	1.0m (40 in.)	2.0m (6.5 ft.)	3.0m (10 ft.)	5.0m (16.4 ft.)
RADIUS™ 48 (RAH48) 	OFC UHS Certified • UL-CL2	Ultra 8K 48Gbps	35	40	50	60	100
SPHERE™ 48 (SPH48) 	OFC • UL-CL2 Uni-Path design	Ultra 8K 48Gbps	60	70	90	110	190
SILVER SPHERE™ 48 (SSP48) 	silver-clad OFC Uni-Path design	Ultra 8K 48Gbps	250	300	400	500	n/a
PLATINUM STARLIGHT® 48 (PSH48) 	solid silver Uni-Path design Isolated power conductor	Ultra 8K 48Gbps	800	1,000	1,500	2,000	n/a

FIBER OPTIC HDMI® CABLES Ethernet / eARC	Conductor material UL Rating	Active Components	HDMI Level	5.0m (16.4 ft.)	10.0m (33 ft.)	15.0m (50 ft.)	20.0m (65.6 ft.)	30.0m (100 ft.)
STARLIGHT® 48 OPTICAL HDMI (SOH48) 	OM3 laser-optimized fibers UHS Certified • UL-CL2/FT4	American II-VI lasers Silicon-Line German chipset	Ultra 8K 48Gbps	320	360	400	450	550
STELLAR® OPTICAL HDMI (STH48) 	OM3 laser-optimized fibers Plenum Rated CMP/FT6 UHS Certified	American II-VI lasers Silicon-Line German chipset VIVIDTECH™ NR System	Ultra 8K 48Gbps	500	550	600	650	750

HDMI® / DVI ADAPTERS					
HDMI Female to HDMI Female (HDMIFF) 17 	HDMI Right (HDMIANGR) or Left Angle (HDMIANGL) 17 	HDMI Female to Mini HDMI Male (MINIHDMI) 17 	HDMI Female to DVI Male (HDMFDVM) 40 	HDMI Male to DVI Female (HDMMDVF) 40 	









HDMI® The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.






All Wireworld Interconnects are available as 5, 6 & 7 channel sets






AUDIO INTERCONNECT PAIRS (2 RCA males to 2 RCA males)	Conductor material	Insulation material	Cable design	Plug Contact materials	0.5m pair (20 in.)	1.0m pair (40 in.)	1.5m pair (5 ft.)	2.0m pair (6.5 ft.)	3.0m pair (10 ft.)	6.0m pair (20 ft.)
STREAM™ (STI) 	oxygen-free copper	COMPOSILEX® 3	Dual DNA Helix®	24K gold/brass	30	36	n/a	42	48	n/a
LUNA™ 8 (LUI) 	oxygen-free copper	COMPOSILEX 3	Tri DNA Helix	24K gold/OFC	65	70	75	80	90	120
SOLSTICE® 8 (SOI) 	silver-plated OFC	COMPOSILEX 3	Tri DNA Helix	24K gold/OFC	87	99	111	123	147	219
OASIS® 8 (OAI) 	oxygen-free copper	COMPOSILEX 3	Tri DNA Helix	silver-clad OFC	130	150	170	190	230	350
EQUINOX® 8 (EQI) 	OCC-7N copper	COMPOSILEX 3	Tri DNA Helix	silver-clad OFC	190	250	310	370	490	850
ECLIPSE™ 8 (ECI) 	OCC-7N copper	COMPOSILEX 3	Quad DNA Helix	silver-clad OFC	400	525	650	775	1,025	1,775
SILVER ECLIPSE™ 8 (SEI) 	OCC-7N silver-clad copper	COMPOSILEX 3	Quad DNA Helix	silver-clad OFC	550	800	1,050	1,300	1,800	3,300
GOLD ECLIPSE™ 8 (GEI) 	solid silver	COMPOSILEX 3	Quad DNA Helix	silver-clad OFC	1,050	1,750	2,450	3,150	4,550	8,750
PLATINUM ECLIPSE™ 8 (PEI) 	OCC-7N solid silver	COMPOSILEX 3	Quad DNA Helix	silver-clad OFC	2,100	3,600	5,100	6,600	9,600	18,600

Add external ground wire to any interconnect or balanced interconnect: \$20























Add external ground wire to any interconnect or balanced interconnect: \$20




BALANCED INTERCONNECT PAIRS (2 XLR females to 2 XLR males)	Conductor material	Insulation material	Cable design	Plug Contact materials	0.5m pair (20 in.)	1.0m pair (40 in.)	1.5m pair (5 ft.)	2.0m pair (6.5 ft.)	3.0m pair (10 ft.)	6.0m pair (20 ft.)
LUNA 8 (LBI) 	oxygen-free copper	COMPOSILEX 3	Tri DNA Helix	silver/copper alloy	95	100	105	110	120	150
SOLSTICE 8 (BSI) 	silver-plated OFC	COMPOSILEX 3	Tri DNA Helix	silver/copper alloy	112	124	136	148	172	244
OASIS 8 (OBI) 	oxygen-free copper	COMPOSILEX 3	Tri DNA Helix	silver/copper alloy	150	170	190	210	250	370
EQUINOX 8 (QBI) 	OCC-7N copper	COMPOSILEX 3	Tri DNA Helix	silver/copper alloy	190	250	310	370	490	850
ECLIPSE 8 (EBI) 	OCC-7N copper	COMPOSILEX 3	Quad DNA Helix	silver/copper alloy	400	525	650	775	1,025	1,775
SILVER ECLIPSE 8 (SBI) 	OCC-7N silver-clad copper	COMPOSILEX 3	Quad DNA Helix	silver/copper alloy	550	800	1,050	1,300	1,800	3,300
GOLD ECLIPSE 8 (GBI) 	solid silver	COMPOSILEX 3	Quad DNA Helix	silver/copper alloy	1,050	1,750	2,450	3,150	4,550	8,750
PLATINUM ECLIPSE 8 (BPI) 	OCC-7N solid silver	COMPOSILEX 3	Quad DNA Helix	silver/copper alloy	2,100	3,600	5,100	6,600	9,600	18,600







SUBWOOFER CABLES (1 RCA male to 1 RCA male)	Conductor material	Insulation material	Cable design	plug contact materials	4.0m (13 ft.)	6.0m (20 ft.)	8.0m (26 ft.)
STREAM SUBWOOFER CABLE (SIM) 	oxygen-free copper	COMPOSILEX® 3	Dual DNA Helix®	24K gold/brass	32	38	n/a
LUNA 8 SUBWOOFER CABLE (LSM) 	oxygen-free copper	COMPOSILEX 3	Tri DNA Helix	24K gold/OFC	50	60	70
SOLSTICE 8 SUBWOOFER CABLE (SSM) 	silver-plated OFC	COMPOSILEX 3	Tri DNA Helix	24K gold/OFC	83	107	131
OASIS 8 SUBWOOFER CABLE (OSM) 	oxygen-free copper	COMPOSILEX 3	Tri DNA Helix	silver-clad OFC	135	175	215
EQUINOX 8 SUBWOOFER CABLE (ESM) 	OCC-7N copper	COMPOSILEX 3	Tri DNA Helix	silver-clad OFC	305	425	545







MINI JACK CABLES (3.5mm stereo mini jack to 2 RCA plugs or 3.5mm to 3.5mm)	Conductor material	Insulation material	Cable design	3.5mm contacts RCA contacts	1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)	3.0m (10 ft.)
iWorld™ (IPA) 	OFC	HDPE	coaxial	24K gold/brass	n/a	20	n/a	n/a
PULSE™ (PUN) 	OFC	COMPOSILEX® 2	DNA Helix	24K gold/brass	36	40	44	52
NANO-ECLIPSE™ (ECN) 	OCC-7N copper	COMPOSILEX 2	DNA Helix	silver-clad alloy silver-clad OFC	175	200	225	275
NANO-SILVER ECLIPSE™ (SEN) 	OCC-7N silver-clad copper	COMPOSILEX 2	DNA Helix	silver-clad alloy silver-clad OFC	225	275	325	425
NANO-PLATINUM ECLIPSE™ Mini Jack to 2 RCAs (PEN) 	OCC-7N solid silver	COMPOSILEX 2	DNA Helix	silver-clad alloy silver-clad OFC	445	570	695	945
Mini Jack Male to Male (NPM)					400	525	650	900
Mini Jack Male to Female (NPF)					400	525	650	900





TONEARM CABLES (Please specify straight or angled DIN when ordering)	Conductor material / Insulation material	Cable design	1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)
SOLSTICE® 8 (SOT – Female DIN plug to 2 RCAs) (BST – Female DIN plug to 2 XLRs) (SOR – RCA to RCA w/ Ground Wire – Subtract \$105) 	silver-plated OFC COMPOSILEX 3	DNA Helix	224	236	248
ECLIPSE™ 8 (ECT – Female DIN plug to 2 RCAs) (EBT – Female DIN plug to 2 XLRs) (ERT – RCA to RCA w/ Ground Wire) 	OCC-7N copper COMPOSILEX 3	DNA Helix	420	480	540
SILVER ECLIPSE™ 8 (SET – Female DIN plug to 2 RCAs) (SBT – Female DIN plug to 2 XLRs) (SRT – RCA to RCA w/ Ground Wire) 	OCC-7N silver-clad copper COMPOSILEX 3	DNA Helix	540	660	780
PLATINUM ECLIPSE™ 8 (PET – Female DIN plug to 2 RCAs) (BPT – Female DIN plug to 2 XLRs) (PRT – RCA to RCA w/ Ground Wire) 	OCC-7N solid silver COMPOSILEX 3	DNA Helix	1,200	1,550	1,900








SPEAKER CABLE - STANDARD PAIRS Spades are standard, bananas optional. SpeakON and 1/4" plugs are also available for Pro applications.		\$/ foot \$/ meter	Conductor, AWG / mm ²	Cable design	Contact materials	2.0m (6.5 ft.)	2.5m (8 ft.)	3.0m (10 ft.)	5.0m (16.4 ft.)	6.0m (20 ft.)
HORIZON™ (HOS) 		1.50/ft. 5/m	OFC 16ga./1.25mm ²	Flexi-Flat™	gold / silver / OFC	90	95	100	120	130
HELICON™ 16 OFC (HES) 		2.40/ft. 8/m	OFC 16ga./1.25mm ²	Dual DNA Helix®	gold / silver / OFC	127	135	143	175	191
HELICON 16 OCC (HCS) 		10.50/ft. 35/m	OCC-7N copper 16ga./1.25mm ²	Dual DNA Helix®	silver-clad OFC	260	295	330	470	540
STREAM™ 8 (STS) UL-CL3/FT4 		2.70/ft. 9/m	OFC 16ga./1.25mm ²	Dual DNA Helix®	gold / silver / OFC	136	145	154	190	208
LUNA™ 8 (LUS) UL-CL3/FT4 		3.60/ft. 12/m	OFC 14ga./2mm ²	Quad DNA Helix	gold / silver / OFC	188	200	212	260	284
SOLSTICE® 8 (SOS) UL-CL3/FT4 		4.80/ft. 16/m	OFC 13ga./2.5mm ²	Quad DNA Helix	gold / silver / OFC	214	230	246	310	342
OASIS® 8 (OAS) UL-CL3/FT4 		9/ft. 30/m	OFC 11ga./4mm ²	Quad DNA Helix	silver-clad OFC	370	400	430	550	610
EQUINOX® 8 (EQS) UL-CL3/FT4 		36/ft. 120/m	OCC-7N copper 11ga./4mm ²	Quad DNA Helix	silver-clad OFC	730	850	970	1,450	1,690
MINI ECLIPSE™ 8 (MES) UL-CL3/FT4 		27/ft. 90/m	OCC-7N copper 13ga./2.5mm ²	Quad DNA Helix	silver-clad OFC	610	700	790	1,150	1,330
ECLIPSE™ 8 (ECS) 		99/ft. 330/m	OCC-7N copper 9ga./6mm ²	Octo DNA Helix	silver-clad OFC	1,920	2,250	2,580	3,900	4,560
SILVER ECLIPSE™ 8 (SES) 		231/ft. 770/m	OCC-7N silver-clad copper 9ga./6mm ²	Octo DNA Helix	silver-clad OFC	3,680	4,450	5,220	8,300	9,840
GOLD ECLIPSE™ 8 (GES) 		750/ft. 2,500/m	solid silver 9ga./6mm ²	Octo DNA Helix	silver-clad OFC	10,700	13,200	15,700	25,700	30,700
PLATINUM ECLIPSE™ 8 (PES) 		1,440/ft. 4,800/m	OCC-7N solid silver 8ga./8mm ²	Octo DNA Helix	silver-clad OFC	20,000	24,800	29,600	48,800	58,400
SPEAKER CABLE - BIWIRED PAIRS Spades are standard, bananas optional. SpeakON and 1/4" plugs are also available for Pro applications.		\$/ foot \$/ meter	Conductor, AWG / mm ²	Cable design	Contact materials	2.0m (6.5 ft.)	2.5m (8 ft.)	3.0m (10 ft.)	5.0m (16.4 ft.)	6.0m (20 ft.)
LUNA 8 (LUB) UL-CL3/FT4 		3.60/ft. 12/m	OFC 14ga./2mm ²	Quad DNA Helix	gold / silver / OFC	228	240	252	300	324
SOLSTICE 8 (SOB) UL-CL3/FT4 		4.80/ft. 16/m	OFC 13ga./2.5mm ²	Quad DNA Helix	gold / silver / OFC	264	280	296	360	392
OASIS 8 (OAB) UL-CL3/FT4 		9/ft. 30/m	OFC 11ga./4mm ²	Quad DNA Helix	silver-clad OFC	470	500	530	650	710
EQUINOX 8 (EQB) UL-CL3/FT4 		36/ft. 120/m	OCC-7N copper 11ga./4mm ²	Quad DNA Helix	silver-clad OFC	830	950	1,170	1,550	1,790
MINI ECLIPSE 8 (MEB) UL-CL3/FT4 		27/ft. 90/m	OCC-7N copper 13ga./2.5mm ²	Quad DNA Helix	silver-clad OFC	710	800	890	1,250	1,430
ECLIPSE 8 (ECB) 		99/ft. 330/m	OCC-7N copper 9ga./6mm ²	Octo DNA Helix	silver-clad OFC	2,120	2,450	2,780	4,100	4,760
SILVER ECLIPSE 8 (SEB) 		231/ft. 770/m	OCC-7N silver-clad copper 9ga./6mm ²	Octo DNA Helix	silver-clad OFC	3,880	4,650	5,420	8,500	10,040
GOLD ECLIPSE 8 (GEB) 		750/ft. 2,500/m	solid silver 9ga./6mm ²	Octo DNA Helix	silver-clad OFC	10,900	13,400	15,900	25,900	30,900
PLATINUM ECLIPSE 8 (PEB) 		1,440/ft. 4,800/m	OCC-7N solid silver 8ga./8mm ²	Octo DNA Helix	silver-clad OFC	20,200	25,000	29,800	49,000	58,600

TWINAX ETHERNET CABLES Patented noise-isolating design. Longer lengths provide greater improvements.		Materials	Cable design	1.0m (40 in.)	2.0m (6.5 ft.)	3.0m (10 ft.)	5.0m (16.4 ft.)	10.0m (32.8 ft.)
CHROMA 8 (CHE) 		23 ga. oxygen-free copper COMPOSILEX® 3	Tite-Shield™ patented triple-shielded design	100	125	150	200	325
STARLIGHT® 8 (STE) 		23 ga. silver-clad OFC COMPOSILEX 3	Tite-Shield™ patented triple-shielded design	275	350	425	575	950
PLATINUM STARLIGHT 8 (PSE) 		23 ga. OCC-7N solid silver COMPOSILEX 3	Tite-Shield™ patented triple-shielded design	900	1,500	2,100	3,300	6,300













COAXIAL DIGITAL AUDIO CABLES (75 ohms, RCA plugs, BNC's optional)	Conductor material	Insulation material	Cable design	Plug Contact materials	0.5m (20 in.)	1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)	3.0m (10 ft.)	6.0m (20 ft.)
CHROMA 8 (CRV) 	oxygen-free copper	COMPOSILEX® 3	DNA Helix®	24K gold / OFC	37	40	43	46	52	70
ULTRAVIOLET 8 (UVV) 	silver-plated OFC	COMPOSILEX 3	DNA Helix	24K gold / OFC	65	70	75	80	90	120
STARLIGHT 8 (STV) 	silver-clad OFC	COMPOSILEX 3	DNA Helix	silver-clad OFC	105	125	145	165	205	325
SILVER STARLIGHT 8 (SSV) 	OCC-7N silver-clad copper	COMPOSILEX 3	DNA Helix	silver-clad OFC	250	300	350	400	500	800
GOLD STARLIGHT® 8 (GSV) 	solid silver	COMPOSILEX 3	DNA Helix	silver-clad OFC	425	600	775	950	1,300	2,350
PLATINUM STARLIGHT 8 (PSV) 	OCC-7N solid silver	COMPOSILEX 3	DNA Helix	silver-clad OFC	1,150	1,900	2,650	3,400	4,900	9,400

BALANCED DIGITAL AUDIO CABLES (110-ohm XLR female to XLR male)	Conductor material	Insulation material	Cable design	Plug contact materials	0.5m (20 in.)	1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)	3.0m (10 ft.)	6.0m (20 ft.)
LUNA 8 (LUA) 	OFC	COMPOSILEX® 3	DNA Helix	silver-clad copper alloy	47.50	50	52.50	55	60	75
SOLSTICE 8 (SOA) 	silver plated OFC	COMPOSILEX 3	DNA Helix	silver-clad copper alloy	56	62	68	74	86	122
MICRO-ECLIPSE 8 (MEA) 	OCC-7N copper	COMPOSILEX 3	DNA Helix	silver-clad copper alloy	170	200	230	260	320	500
MICRO-SILVER ECLIPSE 8 (MSA) 	OCC-7N silver-clad copper	COMPOSILEX 3	DNA Helix	silver-clad copper alloy	240	300	360	420	540	900
MICRO-PLATINUM ECLIPSE 8 (MPA) 	OCC-7N solid silver	COMPOSILEX 3	DNA Helix	silver-clad copper alloy	375	550	725	900	1,250	2,300
PLATINUM STARLIGHT 8 (PSA) 	OCC-7N solid silver	COMPOSILEX 3	DNA Helix	silver-clad copper alloy	1,050	1,800	2,550	3,300	4,800	9,300

TOSLINK OPTICAL - DIGITAL AUDIO	Conductor material	0.5m (20 in.)	1.0m (40 in.)	2.0m (6.5 ft.)	3.0m (10 ft.)	5.0m (16.4 ft.)	8.0m (26 ft.)
NOVA™ Toslink Optical (NTO) 	acrylic monofilament	35	40	50	60	70	n/a
NOVA Toslink to 3.5mm Connector (NMO) 	acrylic monofilament	35	40	50	60	n/a	n/a
SUPERNOVA™ 7 Toslink Optical (STO) 	338 borosilicate glass fibers	230	260	320	380	500	680
SUPERNOVA 7 Toslink to 3.5mm Connector (SMO) 	338 borosilicate glass fibers	230	260	320	n/a	n/a	n/a

USB AUDIO CABLES (All models exceed official USB specifications) 90-0hm impedance		Conductor material	Insulation material	Cable design	0.3m	0.6m	1.0m	2.0m	3.0m
					(1 ft.)	(2 ft.)	(40 in.)	(6.5 ft.)	(10 ft.)
2.0	CHROMA™ 8 USB 2.0 A to B (C2AB) 	OFC	COMPOSILEX 3	Uni-Path™ Isolated power conductor	n/a	30	33	40	48
	CHROMA™ 8 USB 2.0 C to B (C2CB) <i>(Available Sept. 2023)</i> 	OFC	COMPOSILEX 3	Uni-Path™ Isolated power conductor	n/a	n/a	33	n/a	n/a
	STARLIGHT® 8 USB 2.0 A to B (S2AB) 	silver-clad OFC	COMPOSILEX 3	Uni-Path Isolated power conductor	n/a	90	110	130	150
	PLATINUM STARLIGHT® 8 USB 2.0 A to B (P2AB) 	solid silver	COMPOSILEX 3	Uni-Path Isolated power conductor	460	520	600	800	1,000
	PLATINUM STARLIGHT® 8 USB 2.0 C to A (P2CA) 	solid silver	COMPOSILEX 3	Uni-Path Isolated power conductor	n/a	n/a	600	n/a	n/a
3.1	CHROMA 8 USB 3.1 C to C (C31C) 	OFC	COMPOSILEX 3	Uni-Path Isolated power conductor	n/a	58	60	n/a	n/a
	STARLIGHT 8 USB 3.1 C to C (S31C) 	silver-clad OFC	COMPOSILEX 3	Uni-Path Isolated power conductor	n/a	140	180	n/a	n/a

*All items below discontinued. **20% OFF WHILE SUPPLIES LAST** Prices shown are discounted.*

USB AUDIO CABLES (All models exceed official USB specifications) 90-0hm impedance		Conductor material	Insulation material	Cable design	0.3m	0.6m	1.0m	2.0m	3.0m
					(1 ft.)	(2 ft.)	(40 in.)	(6.5 ft.)	(10 ft.)
2.0	CHROMA 8 USB 2.0 A to Micro-B (C2AM) 	OFC	COMPOSILEX 3	Uni-Path™ Isolated power conductor	n/a	24	26.40	32	38.40
	ULTRAVIOLET™ 8 USB 2.0 A to B (U2AB) 	silver-plated OFC	COMPOSILEX 3	Uni-Path Isolated power conductor	n/a	U2AB0.6M n/a 40	48	56	64
	ULTRAVIOLET 8 USB 2.0 A to Micro-B (U2AM) 					n/a	n/a	88	104
	STARLIGHT 8 USB 2.0 A to Micro-B (S2AM) 	silver-clad OFC	COMPOSILEX 3	Uni-Path Isolated power conductor	n/a	n/a	88	104	120
	PLATINUM STARLIGHT® 8 USB 2.0 A to Micro-B (P2AM) 	solid silver	COMPOSILEX 3	Uni-Path Isolated power conductor	368	416	480	640	n/a
	PLATINUM STARLIGHT® 8 USB 2.0 C to Micro-B (P2CM) 	solid silver	COMPOSILEX 3	Uni-Path Isolated power conductor	n/a	n/a	480	n/a	n/a
3.0	CHROMA 8 USB 3.0 A to B (C3AB) 	OFC	COMPOSILEX 3	Uni-Path Isolated power conductor	n/a	36	40	48	56
	CHROMA 8 USB 3.0 A to Micro-B (C3AM) 								
	ULTRAVIOLET 8 USB 3.0 A to B (U3AB) 	silver-plated OFC	COMPOSILEX 3	Uni-Path Isolated power conductor	n/a	56	64	76	88
	ULTRAVIOLET 8 USB 3.0 A to Micro-B (U3AM) 								
	STARLIGHT 8 USB 3.0 A to B (S3AB) 	silver-clad OFC	COMPOSILEX 3	Uni-Path Isolated power conductor	n/a	96	120	144	168
	STARLIGHT 8 USB 3.0 A to Micro-B (S3AM) 								

NOTE: Wireworld Power Cords function as filters, so longer lengths provide greater improvements. We recommend two meters or more for the best performance.

POWER CONDITIONING CORDS – Ultra-quiet, dynamic and flexible. Standard: US, EU, UK wall plug to IEC C13. VDE certified for safety. C19 or PowerCON custom termination available for upcharge.		Conductor material	Insulation material	Cable design	Plug contact material	1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)	3.0m (10 ft.)
STRATUS™ 7 Power Cord (STP)		oxygen-free copper	COMPOSILEX® 2	Fluxfield™	silver-clad copper alloy	110	135	160	210
AURORA™ 7 Power Cord (AUP)		silver-clad OFC	COMPOSILEX2	Fluxfield	silver-clad copper alloy	160	200	240	320
ELECTRA™ 7 Power Cord (ELP)		OCC-7N copper	COMPOSILEX2	Fluxfield	silver-clad copper alloy	260	330	400	540
SILVER ELECTRA™ 7 Power Cord (SEP)		OCC-7N silver-clad copper	COMPOSILEX2	Fluxfield	silver-clad copper alloy	500	625	750	1,000
PLATINUM ELECTRA™ 7 Power Cord (PEP)		OCC-7N solid silver	COMPOSILEX2	Fluxfield	OCC silver-clad copper	2,200	2,900	3,600	5,000
Mini Standard: US, EU wall plug to IEC C7 (Figure 8); UK termination available for \$10 upcharge. Now includes angle adapter.									
STRATUS™ Shielded Mini Power Cord (MSP-S)		oxygen-free copper	COMPOSILEX	Fluxfield	silver-clad copper alloy	70	80	90	n/a
ELECTRA™ Shielded Mini Power Cord (MEP-S)		OCC-7N copper	COMPOSILEX	Fluxfield	silver-clad copper alloy	160	200	240	n/a

POWER CORD CONNECTOR UPGRADE – Standard & custom lengths	POWER CORD ADAPTERS				
<ul style="list-style-type: none"> Silver-clad copper alloy contacts Flat clamp for STP / AUP / ELP / SEP only Standard lengths may be upgraded with this connector All custom length cords and standard length upgrade cords will be priced \$140 higher than with molded plugs <p>SILVER-CLAD OFC CONTACTS, US MALE OR IEC SILVER-CLAD OCC CONTACTS, US MALE OR IEC</p> <p>PCSVRUS 60 PCSVRIEC 60 PCOCCUS 120 PCOCCIEC 120</p>					
	GNDLIFT 4	IECMFG8 8	IECM1F 8	IECM2F 12	ADPC7C8 5

POWER STRIP	
Oxygen-free copper, star-wired, rack mountable shielded power cord extender	<p>MATRIX 2 120</p>

Thank You
We appreciate your business.

