

RETAIL PRICE SHEET

November, 2024





WIREWORLD®



CABLE TECHNOLOGY


Engineered
for
Reality™

All prices shown are in U.S. Dollars.
International prices may vary.

Because we are continually striving to improve our products, all specifications and prices are subject to change without notice.










HDMI® CABLES Ethernet / eARC COMPOSILEX 3 insulation		Conductor material Cable design	HDMI Level	0.6m (2 ft.)	1.0m (40 in.)	2.0m (6.5 ft.)	3.0m (10 ft.)	5.0m (16.4 ft.)
RADIUS™ 48 (RAH48)		OFC UHS Certified • UL-CL2	Ultra 8K 48Gbps	35	40	50	60	100
SPHERE™ 48 (SPH48)		OFC • UL-CL2 Uni-Path design	Ultra 8K 48Gbps	60	70	90	110	190
SILVER SPHERE™ 48 (SSP48)		silver-clad OFC Uni-Path design	Ultra 8K 48Gbps	250	300	400	500	n/a
PLATINUM STARLIGHT® 48 (PSH48)		solid silver Uni-Path design Isolated power conductor	Ultra 8K 48Gbps	800	1,000	1,500	2,000	n/a

FIBER OPTIC HDMI® CABLES Ethernet / eARC		Conductor material UL Rating	Active Components	HDMI Level	5.0m (16.4 ft.)	10.0m (33 ft.)	15.0m (50 ft.)	20.0m (65.6 ft.)	30.0m (100 ft.)
STARLIGHT® 48 OPTICAL HDMI (SOH48)		OM3 laser-optimized fibers UHS Certified • UL-CL2/FT4	American II-VI lasers Silicon-Line German chipset	Ultra 8K 48Gbps	320	360	400	450	550
STELLAR® OPTICAL HDMI (STH48)		OM3 laser-optimized fibers Plenum Rated CMP/FT6 UHS Certified	American II-VI lasers Silicon-Line German chipset VIVIDTECH™ NR System	Ultra 8K 48Gbps	500	550	600	650	750



























The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.







All Wireworld Interconnects are available as 5, 6 & 7 channel sets






AUDIO INTERCONNECT PAIRS (2 RCA males to 2 RCA males)	Conductor material	Insulation material	Cable design	Plug Contact materials	0.5m (20 in.)	0.75m (30 in.)	1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)	3.0m (10 ft.)	6.0m (20 ft.)
STREAM™ 10 (STI) 	oxygen-free copper	COMPOSILEX® 5	Dual DNA Helix®	24K gold/brass	30	n/a	36	n/a	42	48	n/a
LUNA™ 10 (LUI) 	oxygen-free copper	COMPOSILEX 5	Tri DNA Helix	24K gold/OFC	65	n/a	70	75	80	90	120
SOLSTICE® 10 (SOI) 	silver-plated OFC	COMPOSILEX 5	Tri DNA Helix	24K gold/OFC	87	n/a	99	111	123	147	219
OASIS® 10 (OAI) 	oxygen-free copper	COMPOSILEX 5	Tri DNA Helix	silver-clad OFC	140	n/a	160	180	200	240	360
EQUINOX® 10 (EQI) 	OCC-7N copper	COMPOSILEX 5	Tri DNA Helix	silver-clad OFC	210	n/a	270	330	390	510	870
ECLIPSE™ 10 (ECI) 	OCC-7N copper	COMPOSILEX 5	Quad DNA Helix	silver-clad OFC	430	495	560	690	820	1,080	1,860
SILVER ECLIPSE™ 10 (SEI) 	OCC-7N silver-clad copper	COMPOSILEX 5	Quad DNA Helix	silver-clad OFC	600	725	850	1,100	1,350	1,850	3,350
GOLD ECLIPSE™ 10 (GEI) 	solid silver	COMPOSILEX 5	Quad DNA Helix	silver-clad OFC	1,150	1,525	1,900	2,650	3,400	4,900	9,400
PLATINUM ECLIPSE™ 10 (PEI) 	OCC-7N solid silver	COMPOSILEX 5	Quad DNA Helix	silver-clad OFC	2,300	3,100	3,900	5,500	7,100	10,300	19,900






Add external ground wire to any interconnect or balanced interconnect: \$20






BALANCED INTERCONNECT PAIRS (2 XLR females to 2 XLR males)		Conductor material	Insulation material	Cable design	Plug Contact materials	0.5m (20 in.)	0.75m (30 in.)	1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)	3.0m (10 ft.)	6.0m (20 ft.)
LUNA™ 10 (LBI) 	oxygen-free copper	COMPOSILEX 5	Tri DNA Helix	silver/copper alloy	95	n/a	100	105	110	120	150	
SOLSTICE® 10 (BSI) 	silver-plated OFC	COMPOSILEX 5	Tri DNA Helix	silver/copper alloy	112	n/a	124	136	148	172	244	
OASIS® 10 (OBI) 	oxygen-free copper	COMPOSILEX 5	Tri DNA Helix	silver/copper alloy	160	n/a	180	200	220	260	380	
EQUINOX® 10 (QBI) 	OCC-7N copper	COMPOSILEX 5	Tri DNA Helix	silver/copper alloy	210	n/a	270	330	390	510	870	
ECLIPSE™ 10 (EBI) 	OCC-7N copper	COMPOSILEX 5	Quad DNA Helix	silver/copper alloy	430	495	560	690	820	1,080	1,860	
SILVER ECLIPSE™ 10 (SBI) 	OCC-7N silver-clad copper	COMPOSILEX 5	Quad DNA Helix	silver/copper alloy	600	725	850	1,100	1,350	1,850	3,350	
GOLD ECLIPSE™ 10 (GBI) 	solid silver	COMPOSILEX 5	Quad DNA Helix	silver/copper alloy	1,150	1,525	1,900	2,650	3,400	4,900	9,400	
PLATINUM ECLIPSE™ 10 (BPI) 	OCC-7N solid silver	COMPOSILEX 5	Quad DNA Helix	silver/copper alloy	2,300	3,100	3,900	5,500	7,100	10,300	19,900	
AUDIO INTERCONNECT PAIRS – RCA to XLR (2 RCA males to 2 XLR males)		Conductor material	Insulation material	Cable design	Plug Contact materials	0.5m (20 in.)	0.75m (30 in.)	1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)	3.0m (10 ft.)	6.0m (20 ft.)
LUNA™ 10 (LUI-RX) 	oxygen-free copper	COMPOSILEX 5	Tri DNA Helix	24K gold/OFC silver/copper alloy	80	n/a	85	90	95	105	135	
SOLSTICE® 10 (SOI-RX) 	silver-plated OFC	COMPOSILEX 5	Tri DNA Helix	24K gold/OFC silver/copper alloy	99.50	n/a	111.50	123.50	135.50	159.50	231.50	
OASIS® 10 (OAI-RX) 	oxygen-free copper	COMPOSILEX 5	Tri DNA Helix	silver-clad OFC silver/copper alloy	150	n/a	170	190	210	250	370	
EQUINOX® 10 (EQI-RX) 	OCC-7N copper	COMPOSILEX 5	Tri DNA Helix	silver-clad OFC silver/copper alloy	210	n/a	270	330	390	510	870	
ECLIPSE™ 10 (ECI-RX) 	OCC-7N copper	COMPOSILEX 5	Quad DNA Helix	silver-clad OFC silver/copper alloy	430	495	560	690	820	1,080	1,860	
SILVER ECLIPSE™ 10 (SEI-RX) 	OCC-7N silver-clad copper	COMPOSILEX 5	Quad DNA Helix	silver-clad OFC silver/copper alloy	600	725	850	1,100	1,350	1,850	3,350	
GOLD ECLIPSE™ 10 (GEI-RX) 	solid silver	COMPOSILEX 5	Quad DNA Helix	silver-clad OFC silver/copper alloy	1,150	1,525	1,900	2,650	3,400	4,900	9,400	
PLATINUM ECLIPSE™ 10 (PEI-RX) 	OCC-7N solid silver	COMPOSILEX 5	Quad DNA Helix	silver-clad OFC silver/copper alloy	2,300	3,100	3,900	5,500	7,100	10,300	19,900	













AUDIO INTERCONNECT PAIRS – XLR to RCA (2 XLR females to 2 RCA males)	Conductor material	Insulation material	Cable design	Plug Contact materials	0.5m (20 in.)	0.75m (30 in.)	1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)	3.0m (10 ft.)	6.0m (20 ft.)
LUNA™ 10 (LUI-XR) 	oxygen-free copper	COMPOSILEX 5	Tri DNA Helix	silver/copper alloy 24K gold/OFC	80	n/a	85	90	95	105	135
SOLSTICE® 10 (SOI-XR) 	silver-plated OFC	COMPOSILEX 5	Tri DNA Helix	silver/copper alloy 24K gold/OFC	99.50	n/a	111.50	123.50	135.50	159.50	231.50
OASIS® 10 (OAI-XR) 	oxygen-free copper	COMPOSILEX 5	Tri DNA Helix	silver/copper alloy silver-clad OFC	150	n/a	170	190	210	250	370
EQUINOX® 10 (EQI-XR) 	OCC-7N copper	COMPOSILEX 5	Tri DNA Helix	silver/copper alloy silver-clad OFC	210	n/a	270	330	390	510	870
ECLIPSE™ 10 (ECI-XR) 	OCC-7N copper	COMPOSILEX 5	Quad DNA Helix	silver/copper alloy silver-clad OFC	430	495	560	690	820	1,080	1,860
SILVER ECLIPSE™ 10 (SEI-XR) 	OCC-7N silver-clad copper	COMPOSILEX 5	Quad DNA Helix	silver/copper alloy silver-clad OFC	600	725	850	1,100	1,350	1,850	3,350
GOLD ECLIPSE™ 10 (GEI-XR) 	solid silver	COMPOSILEX 5	Quad DNA Helix	silver/copper alloy silver-clad OFC	1,150	1,525	1,900	2,650	3,400	4,900	9,400
PLATINUM ECLIPSE™ 10 (PEI-XR) 	OCC-7N solid silver	COMPOSILEX 5	Quad DNA Helix	silver/copper alloy silver-clad OFC	2,300	3,100	3,900	5,500	7,100	10,300	19,900









AUDIO INTERCONNECT PAIRS w/GROUNDWIRE (2 RCA males to 2 RCA males)	Conductor material	Insulation material	Cable design	Plug Contact materials	0.5m (20 in.)	0.75m (30 in.)	1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)	3.0m (10 ft.)	6.0m (20 ft.)
*LUNA™ 10 (LUI-G) 	oxygen-free copper	COMPOSILEX 5	Tri DNA Helix	24K gold/OFC	85	n/a	90	95	100	110	140
*SOLSTICE® 10 (SOI-G) 	silver-plated OFC	COMPOSILEX 5	Tri DNA Helix	24K gold/OFC	107	n/a	119	131	143	167	239
OASIS® 10 (OAI-G) 	oxygen-free copper	COMPOSILEX 5	Tri DNA Helix	silver-clad OFC	160	n/a	180	200	220	260	380
EQUINOX® 10 (EQI-G) 	OCC-7N copper	COMPOSILEX 5	Tri DNA Helix	silver-clad OFC	230	n/a	290	350	410	530	890
ECLIPSE™ 10 (ECI-G) 	OCC-7N copper	COMPOSILEX 5	Quad DNA Helix	silver-clad OFC	450	515	580	710	840	1,100	1,880
SILVER ECLIPSE™ 10 (SEI-G) 	OCC-7N silver-clad copper	COMPOSILEX 5	Quad DNA Helix	silver-clad OFC	620	745	870	1,120	1,370	1,870	3,370
GOLD ECLIPSE™ 10 (GEI-G) 	solid silver	COMPOSILEX 5	Quad DNA Helix	silver-clad OFC	1,170	1,545	1,920	2,670	3,420	4,920	9,420
PLATINUM ECLIPSE™ 10 (PEI-G) 	OCC-7N solid silver	COMPOSILEX 5	Quad DNA Helix	silver-clad OFC	2,320	3,120	3,920	5,520	7,120	10,320	19,920




SUBWOOFER CABLES (1 RCA male to 1 RCA male)	Conductor material	Insulation material	Cable design	plug contact materials	2.0m (6.5 ft.)	3.0m (10 ft.)	4.0m (13 ft.)	6.0m (20 ft.)	8.0m (26 ft.)
STREAM™ 10 SUBWOOFER CABLE (SIM) 	oxygen-free copper	COMPOSILEX® 5	Dual DNA Helix®	24K gold/brass	n/a	n/a	32	38	n/a
LUNA™ 10 SUBWOOFER CABLE (LSM) 	oxygen-free copper	COMPOSILEX 5	Tri DNA Helix	24K gold/OFC	40	45	50	60	70
SOLSTICE® 10 SUBWOOFER CABLE (SSM) 	silver-plated OFC	COMPOSILEX 5	Tri DNA Helix	24K gold/OFC	59	71	83	107	131
OASIS® 10 SUBWOOFER CABLE (OSM) 	oxygen-free copper	COMPOSILEX 5	Tri DNA Helix	silver-clad OFC	105	125	145	185	225
EQUINOX® 10 SUBWOOFER CABLE (ESM) 	OCC-7N copper	COMPOSILEX 5	Tri DNA Helix	silver-clad OFC	195	255	315	435	555







MINI JACK CABLES (3.5mm stereo mini jack to 2 RCA plugs or 3.5mm to 3.5mm)	Conductor material	Insulation material	Cable design	3.5mm contacts RCA contacts	1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)	3.0m (10 ft.)
iWorld™ (IPA) 	OFC	HDPE	coaxial	24K gold/brass	n/a	20	n/a	n/a
PULSE™ (PUN) 	OFC	COMPOSILEX® 2	DNA Helix	24K gold/brass	36	40	44	52
NANO-ECLIPSE™ (ECN) 	OCC-7N copper	COMPOSILEX 2	DNA Helix	silver-clad alloy silver-clad OFC	175	200	225	275
NANO-SILVER ECLIPSE™ (SEN) 	OCC-7N silver-clad copper	COMPOSILEX 2	DNA Helix	silver-clad alloy silver-clad OFC	225	275	325	425
NANO-PLATINUM ECLIPSE™ Mini Jack to 2 RCAs (PEN) 	OCC-7N solid silver	COMPOSILEX 2	DNA Helix	silver-clad alloy silver-clad OFC	445	570	695	945
Mini Jack Male to Male (NPM)					400	525	650	900
Mini Jack Male to Female (NPF)					400	525	650	900





TONARM CABLES (Please specify straight or angled DIN when ordering)	Conductor material / Insulation material	Cable design	1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)
LUNA™ 10 LUT – Female DIN plug to 2 RCAs LBT – Female DIN plug to 2 XLRs LUI-G – RCA to RCA w/ Ground Wire – *See page 3 	silver-plated OFC COMPOSILEX 5	DNA Helix	180	185	190
SOLSTICE® 10 SOT – Female DIN plug to 2 RCAs BST – Female DIN plug to 2 XLRs SOI-G – RCA to RCA w/ Ground Wire – *See page 3 	silver-plated OFC COMPOSILEX 5	DNA Helix	224	236	248
ECLIPSE™ 10 ECT – Female DIN plug to 2 RCAs EBT – Female DIN plug to 2 XLRs ERT – RCA to RCA w/ Ground Wire 	OCC-7N copper COMPOSILEX 5	DNA Helix	420	480	540
SILVER ECLIPSE™ 10 SET – Female DIN plug to 2 RCAs SBT – Female DIN plug to 2 XLRs SRT – RCA to RCA w/ Ground Wire 	OCC-7N silver-clad copper COMPOSILEX 5	DNA Helix	540	660	780
PLATINUM ECLIPSE™ 10 PET – Female DIN plug to 2 RCAs BPT – Female DIN plug to 2 XLRs PRT – RCA to RCA w/ Ground Wire 	OCC-7N solid silver COMPOSILEX 5	DNA Helix	1,200	1,550	1,900





SPEAKER CABLE - STANDARD PAIRS Spades are standard, bananas optional. SpeakON and 1/4" plugs are also available for Pro applications.	\$/ foot \$/ meter	Conductor, AWG / mm ²	Cable design	Contact materials	2.0m (6.5 ft.)	2.5m (8 ft.)	3.0m (10 ft.)	5.0m (16.4 ft.)	6.0m (20 ft.)
HORIZON™ (HOS) 	1.50/ft. 5/m	OFC 16ga./1.25mm ²	Flexi-Flat™	gold / silver / OFC	70	75	80	100	110
HELICON™ 16X OFC (HES) 	2.40/ft. 8/m	OFC 16ga./1.25mm ²	Dual DNA Helix®	gold / silver / OFC	102	110	118	150	166
HELICON 16X OCC (HCS) 	10.50/ft. 35/m	OCC-7N copper 16ga./1.25mm ²	Dual DNA Helix®	silver-clad OFC	230	265	300	440	510
STREAM™ 10 (STS) UL-CL3/FT4 	2.70/ft. 9/m	OFC 16ga./1.25mm ²	Dual DNA Helix®	gold / silver / OFC	116	125	134	170	188
LUNA™ 10 (LUS) UL-CL3/FT4 	3.60/ft. 12/m	OFC 14ga./2mm ²	Quad DNA Helix	gold / silver / OFC	166	180	194	250	278
SOLSTICE® 10 (SOS) UL-CL3/FT4 	4.80/ft. 16/m	OFC 13ga./2.5mm ²	Quad DNA Helix	gold / silver / OFC	192	210	228	300	336
OASIS® 10 (OAS) UL-CL3/FT4 	9/ft. 30/m	OFC 11ga./4mm ²	Quad DNA Helix	silver-clad OFC	440	475	510	650	720
EQUINOX® 10 (EQS) UL-CL3/FT4 	36/ft. 120/m	OCC-7N copper 11ga./4mm ²	Quad DNA Helix	silver-clad OFC	860	1,000	1,140	1,700	1,980
MINI ECLIPSE™ 10 (MES) UL-CL3/FT4 	27/ft. 90/m	OCC-7N copper 13ga./2.5mm ²	Quad DNA Helix	silver-clad OFC	700	800	900	1,300	1,500
ECLIPSE™ 10 (ECS) 	99/ft. 330/m	OCC-7N copper 9ga./6mm ²	Octo DNA Helix	silver-clad OFC	2,100	2,450	2,800	4,200	4,900
SILVER ECLIPSE™ 10 (SES) 	231/ft. 770/m	OCC-7N silver-clad copper 9ga./6mm ²	Octo DNA Helix	silver-clad OFC	4,100	4,950	5,800	9,200	10,900
PLATINUM ECLIPSE™ 10 (PES) 	1,440/ft. 4,800/m	OCC-7N solid silver 8ga./8mm ²	Octo DNA Helix	silver-clad OFC	23,300	28,900	34,500	56,900	68,100









SPEAKER CABLE - BIWIRED PAIRS Spades are standard, bananas optional. SpeakON and 1/4" plugs are also available for Pro applications.	\$/ foot \$/ meter	Conductor, AWG / mm ²	Cable design	Contact materials	2.0m (6.5 ft.)	2.5m (8 ft.)	3.0m (10 ft.)	5.0m (16.4 ft.)	6.0m (20 ft.)
LUNA 10 (LUB) UL-CL3/FT4 	3.60/ft. 12/m	OFC 14ga./2mm ²	Quad DNA Helix	gold / silver / OFC	206	220	234	290	318
SOLSTICE 10 (SOB) UL-CL3/FT4 	4.80/ft. 16/m	OFC 13ga./2.5mm ²	Quad DNA Helix	gold / silver / OFC	232	250	268	340	376
OASIS 10 (OAB) UL-CL3/FT4 	9/ft. 30/m	OFC 11ga./4mm ²	Quad DNA Helix	silver-clad OFC	540	575	610	750	820
EQUINOX 10 (EQB) UL-CL3/FT4 	36/ft. 120/m	OCC-7N copper 11ga./4mm ²	Quad DNA Helix	silver-clad OFC	960	1,100	1,240	1,800	2,080
MINI ECLIPSE 10 (MEB) UL-CL3/FT4 	27/ft. 90/m	OCC-7N copper 13ga./2.5mm ²	Quad DNA Helix	silver-clad OFC	800	900	1,000	1,400	1,600
ECLIPSE 10 (ECB) 	99/ft. 330/m	OCC-7N copper 9ga./6mm ²	Octo DNA Helix	silver-clad OFC	2,300	2,650	3,000	4,400	5,100
SILVER ECLIPSE 10 (SEB) 	231/ft. 770/m	OCC-7N silver-clad copper 9ga./6mm ²	Octo DNA Helix	silver-clad OFC	4,300	5,150	6,000	9,400	11,100
PLATINUM ECLIPSE 10 (PEB) 	1,440/ft. 4,800/m	OCC-7N solid silver 8ga./8mm ²	Octo DNA Helix	silver-clad OFC	23,500	29,100	34,700	57,100	68,300

TWINAX ETHERNET CABLES Patented noise-isolating design. Longer lengths provide greater improvements.		Materials	Cable design	1.0m (40 in.)	2.0m (6.5 ft.)	3.0m (10 ft.)	5.0m (16.4 ft.)	10.0m (32.8 ft.)
CHROMA 10 (CHE) 		23 ga. oxygen-free copper COMPOSILEX® 5	Tite-Shield™ patented triple-shielded design	120	145	170	220	345
STARLIGHT® 10 (STE) 		23 ga. silver-clad OFC COMPOSILEX 5	Tite-Shield™ patented triple-shielded design	315	390	465	615	990
PLATINUM STARLIGHT 10 (PSE) 		23 ga. OCC-7N solid silver COMPOSILEX 5	Tite-Shield™ patented triple-shielded design	1,000	1,600	2,200	3,400	6,400








COAXIAL DIGITAL AUDIO CABLES (75 ohms, RCA plugs, BNC's optional)	Conductor material	Insulation material	Cable design	Plug Contact materials	0.5m (20 in.)	1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)	3.0m (10 ft.)	6.0m (20 ft.)
CHROMA 10 (CRV) 	oxygen-free copper	COMPOSILEX® 5	DNA Helix®	24K gold / OFC	37	40	43	46	52	70
ULTRAVIOLET 10 (UVV) 	silver-plated OFC	COMPOSILEX 5	DNA Helix	24K gold / OFC	75	80	85	90	100	130
STARLIGHT 10 (STV) 	silver-clad OFC	COMPOSILEX 5	DNA Helix	silver-clad OFC	120	140	160	180	220	340
SILVER STARLIGHT 10 (SSV) 	OCC-7N silver-clad copper	COMPOSILEX 5	DNA Helix	silver-clad OFC	300	350	400	450	550	850
GOLD STARLIGHT® 10 (GSV) 	solid silver	COMPOSILEX 5	DNA Helix	silver-clad OFC	500	700	900	1,100	1,500	2,700
PLATINUM STARLIGHT 10 (PSV) 	OCC-7N solid silver	COMPOSILEX 5	DNA Helix	silver-clad OFC	1,250	2,000	2,750	3,500	5,000	9,500

BALANCED DIGITAL AUDIO CABLES (110-ohm XLR female to XLR male)	Conductor material	Insulation material	Cable design	Plug contact materials	0.5m (20 in.)	1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)	3.0m (10 ft.)	6.0m (20 ft.)
MICRO-ECLIPSE 10 (MEA) 	OCC-7N copper	COMPOSILEX 5	DNA Helix	silver-clad copper alloy	180	210	240	270	330	510
MICRO-SILVER ECLIPSE 10 (MSA) 	OCC-7N silver-clad copper	COMPOSILEX 5	DNA Helix	silver-clad copper alloy	260	320	380	440	560	920
MICRO-PLATINUM ECLIPSE 10 (MPA) 	OCC-7N solid silver	COMPOSILEX 5	DNA Helix	silver-clad copper alloy	425	600	775	950	1,300	2,350
PLATINUM STARLIGHT 10 (PSA) 	OCC-7N solid silver	COMPOSILEX 5	DNA Helix	silver-clad copper alloy	1,100	1,850	2,600	3,350	4,850	9,350


TOSLINK OPTICAL - DIGITAL AUDIO	Conductor material	0.5m (20 in.)	1.0m (40 in.)	2.0m (6.5 ft.)	3.0m (10 ft.)	5.0m (16.4 ft.)	8.0m (26 ft.)
NOVA™ Toslink Optical (NTO) 	acrylic monofilament	35	40	50	60	70	n/a
NOVA Toslink to 3.5mm Connector (NMO) 	acrylic monofilament	35	40	50	60	n/a	n/a
SUPERNOVA™ Toslink Optical (STO) 	338 borosilicate glass fibers	260	290	350	410	530	710
SUPERNOVA Toslink to 3.5mm Connector (SMO) 	338 borosilicate glass fibers	260	290	350	n/a	n/a	n/a

USB AUDIO CABLES (All models exceed official USB specifications) 90-0hm impedance		Conductor material	Insulation material	Cable design	0.3m	0.6m	1.0m	2.0m	3.0m
					(1 ft.)	(2 ft.)	(40 in.)	(6.5 ft.)	(10 ft.)
2.0	CHROMA™ 8 USB 2.0 A to B (C2AB) 	OFC	COMPOSILEX 3	Uni-Path™ Isolated power conductor	n/a	30	33	40	48
	CHROMA™ 8 USB 2.0 C to B (C2CB) 	OFC	COMPOSILEX 3	Uni-Path™ Isolated power conductor	n/a	n/a	33	n/a	n/a
	STARLIGHT® 8 USB 2.0 A to B (S2AB) 	silver-clad OFC	COMPOSILEX 3	Uni-Path Isolated power conductor	n/a	90	110	130	150
	STARLIGHT® 8 USB 2.0 C to B (S2CB) 	silver-clad OFC	COMPOSILEX 3	Uni-Path Isolated power conductor	n/a	90	110	130	150
	PLATINUM STARLIGHT® 8 USB 2.0 A to B (P2AB) 	solid silver	COMPOSILEX 3	Uni-Path Isolated power conductor	460	520	600	800	1,000
	PLATINUM STARLIGHT® 8 USB 2.0 C to A (P2CA) 	solid silver	COMPOSILEX 3	Uni-Path Isolated power conductor	n/a	n/a	600	n/a	n/a
3.1	CHROMA 8 USB 3.1 C to C (C31C) 	OFC	COMPOSILEX 3	Uni-Path Isolated power conductor	n/a	58	60	n/a	n/a
	STARLIGHT 8 USB 3.1 C to C (S31C) 	silver-clad OFC	COMPOSILEX 3	Uni-Path Isolated power conductor	n/a	140	180	n/a	n/a

NOTE: Wireworld Power Cords function as filters, so longer lengths provide greater improvements. We recommend two meters or more for the best performance.

POWER CONDITIONING CORDS – Ultra-quiet, dynamic and flexible. Standard: US, EU, UK wall plug to IEC C13. VDE certified for safety. C19 or PowerCON custom termination available for upcharge.		Conductor material	Insulation material	Cable design	Plug contact material	1.0m	1.5m	2.0m	3.0m
						(40 in.)	(5 ft.)	(6.5 ft.)	(10 ft.)
STRATUS™ 10 Power Cord (STP) 		oxygen-free copper	COMPOSILEX® 5	Fluxfield™	silver-clad copper alloy	130	155	180	230
AURORA™ 10 Power Cord (AUP) 		silver-clad OFC	COMPOSILEX 5	Fluxfield	silver-clad copper alloy	180	220	260	340
ELECTRA™ 10 Power Cord (ELP) 		OCC-7N copper	COMPOSILEX 5	Fluxfield	silver-clad copper alloy	310	395	480	650
SILVER ELECTRA™ 10 Power Cord (SEP) 		OCC-7N silver-clad copper	COMPOSILEX 5	Fluxfield	silver-clad copper alloy	525	662.50	800	1,072
PLATINUM ELECTRA™ 10 Power Cord (PEP) 		OCC-7N solid silver	COMPOSILEX 5	Fluxfield	OCC silver-clad copper	2,400	3,200	4,000	5,600
Mini Standard: US, EU wall plug to IEC C7 (Figure 8); UK termination available for \$10 upcharge. Now includes angle adapter.									
STRATUS™ 10 Shielded Mini Power Cord (MSP-S) 		oxygen-free copper	COMPOSILEX	Fluxfield	silver-clad copper alloy	70	80	90	115
ELECTRA™ 10 Shielded Mini Power Cord (MEP-S) 		OCC-7N copper	COMPOSILEX	Fluxfield	silver-clad copper alloy	160	200	240	320

POWER CORD CONNECTOR UPGRADE – Standard & custom lengths				POWER CORD ADAPTERS				
<ul style="list-style-type: none"> Silver-clad copper alloy contacts Flat clamp for STP / AUP / ELP / SEP only Standard lengths may be upgraded with this connector All custom length cords and standard length upgrade cords will be priced \$140 higher than with molded plugs 				<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">  ADPC14C5 8 </div> <div style="text-align: center;">  IECMFG8 8 </div> <div style="text-align: center;">  IECM1F 8 </div> <div style="text-align: center;">  IECM2F 12 </div> <div style="text-align: center;">  ADPC7C8 5 </div> </div>				
SILVER-CLAD COPPER ALLOY CONTACTS. US MALE OR IEC PCSVRUS 60 PCSVRIEC 60		SILVER-CLAD OCC COPPER CONTACTS. US MALE OR IEC PCOCCUS 120 PCOCCIEC 120						

POWER STRIP	
Oxygen-free copper, star-wired,	rack mountable shielded power cord extender
	
MATRIX 2 120	

Thank You

We appreciate your business.

