




RETAIL PRICE SHEET





March 15, 2013

All prices shown are in U.S. Dollars.
International prices may vary.





WIREWORLD®
CABLE TECHNOLOGY

Engineered
for
Reality™

ALL WIREWORLD HDMI CABLES EXCEED HDMI V1.4 HIGH SPEED WITH ETHERNET SPECIFICATIONS, COVERING ALL 3D & UltraHD 4K FORMATS													
FLAT HDMI CABLES (UL-CL3 / CSA-FT4)		Conductor material Cable design	0.3m (1 ft.)	0.5m (20 in.)	1.0m (40 in.)	2.0m (6.5 ft.)	3.0m (10 ft.)	5.0m (16.4 ft.)	7.0m (23 ft.)	9.0m (30 ft.)	12.0m (40 ft.)	15.0m (50 ft.)	20.0m (65.6 ft.)
ISLAND™ 7 HDMI (IHH) 		copper 16-conductor Symmetricon®	26	30	35	42	49	63	active 120	active 140	active 170	n/a	n/a
CHROMA™ 7 HDMI (CHH) 		oxygen-free copper 16-conductor Symmetricon	46	50	60	70	80	100	120	150	active 200	active 245	n/a
ULTRAVIOLET™ 7 HDMI (UHH) 		silver-plated OFC 16-conductor Symmetricon	100	n/a	120	145	170	220	270	320	active 395	active 470	active 595
STARLIGHT® 7 HDMI (SHH) 		silver-plated OFC 24-conductor DNA Helix®	170	n/a	200	250	300	400	500	600	active 750	active 900	active 1,150
SILVER STARLIGHT® 7 HDMI (SSH) 		silver-clad OFC 24-conductor DNA Helix	270	290	350	475	600	850	1,100	1,350	active 1,725	active 2,100	active 2,725
PLATINUM STARLIGHT® 7 HDMI (PSH) 		solid silver 24-conductor DNA Helix	500	700	1,000	1,500	2,000	3,000	4,000	5,000	active 6,500	active 8,000	active 10,500
HDMI ADAPTERS									3D / HDMI v1.4 				
Female to Female HDMIIF 17 		Right Angle HDMIANGL 17 		HDMI to Mini HDMI MINIHDMI 17 				HDMI over CAT5e Transmitter + Receiver HDCATBOX 380 					
USB 2.0 AUDIO CABLES (All exceed USB 2.0 High Speed Specifications)			Conductor material	Insulation material	Cable design	0.3m (1 ft.)	0.5m (20 in.)	1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)	3.0m (10 ft.)	5.0m (16.4 ft.)	
ULTRAVIOLET 7 USB A to B (USB) 			silver-plated OFC	Composilex® 2	4-conductor Symmetricon	43	45	50	n/a	60	70	90	
ULTRAVIOLET 7 USB A to mini B (USM) 						n/a	45	50	n/a	60	n/a	n/a	
STARLIGHT 7 USB A to B (STB) 			silver-clad OFC	Composilex 2	4-conductor Symmetricon	85	90	100	n/a	120	140	180	
STARLIGHT 7 USB A to mini B (STM) 						n/a	90	100	n/a	120	n/a	n/a	
SILVER STARLIGHT USB A to B (SSB) 			silver-clad OFC	foamed PE	6-conductor DNA Helix	265	275	300	325	350	400	500	
SILVER STARLIGHT USB A to mini B (SUM) 						n/a	275	300	n/a	350	n/a	n/a	
PLATINUM STARLIGHT USB A to B (PSB) 			solid silver	foamed PE	6-conductor DNA Helix	460	500	600	700	800	1,000	1,400	
PLATINUM STARLIGHT USB A to mini B (PSM) 						n/a	500	600	n/a	800	n/a	n/a	
USB 3.0 SUPERSPEED AUDIO CABLES				Conductor material	Insulation material	Cable design	0.5m (20 in.)	1.0m (40 in.)	2.0m (6.5 ft.)	3.0m (10 ft.)	5.0m (16.4 ft.)		
STARLIGHT USB3.0 A to B (STX) 				silver-clad OFC	foamed PE	12-conductor Symmetricon	105	120	150	180	240		
STARLIGHT USB3.0 A to MICRO-B (STZ) 							105	120	150	n/a	n/a		
MINI JACK CABLES (3.5mm stereo mini jack to 2 RCA plugs or 3.5mm to 3.5mm)				Conductor material	Insulation material	Cable design	3.5mm contacts RCA contacts		1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)		
iWorld™ (IPA) 				OFC	HDPE	coaxial	24K gold-plated		n/a	20	n/a		
LUNA™ 7 (LUM) 				OFC	Composilex 2	DNA Helix	silver-clad alloy gold / silver / OFC		42	46	50		
SOLSTICE® 7 (SOM) 				silver/OFC	Composilex 2	DNA Helix	silver-clad alloy gold / silver / OFC		60	70	80		
ECLIPSE™ 7 (ECM) 				OCC copper	Composilex 2	DNA Helix	silver-clad alloy silver-clad OFC		110	135	160		
SILVER ECLIPSE™ 7 (SEM) 				silver-clad OCC copper	Composilex 2	DNA Helix	silver-clad alloy silver-clad OFC		180	230	280		
PLATINUM ECLIPSE™ 7 (PEM) 				OCC solid silver	Composilex 2	DNA Helix	silver-clad alloy silver-clad OFC		640	860	1080		

AUDIO INTERCONNECT PAIRS (2 RCA males to 2 RCA males)		Conductor material	Insulation material	Cable design	Plug Contact materials	0.5m pair (20 in.)	1.0m pair (40 in.)	1.5m pair (5 ft.)	2.0m pair (6.5 ft.)	3.0m pair (10 ft.)	6.0m pair (20 ft.)
TERRA™ (TEI) 		oxygen-free copper	HDPE	Flexi-Flat™	gold/nickel/brass	n/a	20	23	26	32	50
LUNA™ 7 (LUI) 		oxygen-free copper	Composilex® 2	DNA Dual Helix®	gold/silver/OFC	36	40	44	48	56	80
SOLSTICE® 7 (SOI) 		silver-plated OFC	Composilex 2	DNA Dual Helix	gold/silver/OFC	52	64	76	88	112	184
OASIS® 7 (OAI) 		oxygen-free copper	Composilex 2	DNA Quad Helix®	silver-clad OFC	85	110	135	160	210	360
EQUINOX® 7 (EQI) 		OCC copper	Composilex 2	DNA Quad Helix	silver-clad OFC	130	200	270	340	480	900
ECLIPSE™ 7 (ECI) 		OCC copper	Composilex 2	DNA Quad Helix	silver-clad OFC	325	450	575	700	950	1,700
SILVER ECLIPSE™ 7 (SEI) 		OCC silver-clad copper	Composilex 2	DNA Quad Helix	silver-clad OFC	450	700	950	1,200	1,700	3,200
GOLD ECLIPSE™ 7 (GEI) 		solid silver	Composilex 2	DNA Quad Helix	silver-clad OFC	900	1,600	2,300	3,000	4,400	8,600
PLATINUM ECLIPSE™ 7 (PEI) 		OCC solid silver	Composilex 2	DNA Quad Helix	silver-clad OFC	1,700	3,000	4,300	5,600	8,200	16,000
BALANCED INTERCONNECT PAIRS (2 XLR females to 2 XLR males)		Conductor material	Insulation material	Cable design	Plug Contact materials	0.5m pair (20 in.)	1.0m pair (40 in.)	1.5m pair (5 ft.)	2.0m pair (6.5 ft.)	3.0m pair (10 ft.)	6.0m pair (20 ft.)
LUNA 7 (LBI) 		oxygen-free copper	Composilex 2	DNA Tri Helix®	silver-clad alloy	93	101	109	117	133	181
OASIS 7 (OBI) 		oxygen-free copper	Composilex 2	DNA Quad Helix	silver-clad alloy	110	135	160	185	235	385
EQUINOX 7 (QBI) 		OCC copper	Composilex 2	DNA Quad Helix	silver-clad alloy	155	225	295	365	505	925
ECLIPSE 7 (EBI) 		OCC copper	Composilex 2	DNA Quad Helix	silver-clad alloy	325	450	575	700	950	1,700
SILVER ECLIPSE 7 (SBI) 		OCC silver-clad copper	Composilex 2	DNA Quad Helix	silver-clad alloy	450	700	950	1,200	1,700	3,200
GOLD ECLIPSE 7 (GBI) 		solid silver	Composilex 2	DNA Quad Helix	silver-clad alloy	900	1,600	2,300	3,000	4,400	8,600
PLATINUM ECLIPSE 7 (BPI) 		OCC solid silver	Composilex 2	DNA Quad Helix	silver-clad alloy	1,700	3,000	4,300	5,600	8,200	16,000
SUBWOOFER CABLES (1 RCA male to 1 RCA male)			Conductor material	Insulation material	Cable design	plug contact materials		4.0m (13 ft.)	6.0m (20 ft.)	8.0m (26 ft.)	
TERRA SUBWOOFER CABLE (TSM) 			oxygen-free copper	HDPE	Flexi-Flat	gold / nickel / brass		25	30	35	
LUNA 7 SUBWOOFER CABLE (LSM) 			oxygen-free copper	Composilex 2	DNA Dual Helix	gold / silver / OFC		36	44	52	
SOLSTICE 7 SUBWOOFER CABLE (SSM) 			silver-plated OFC	Composilex 2	DNA Dual Helix	gold / silver / OFC		73	97	121	
OASIS 7 SUBWOOFER CABLE (OSM) 			oxygen-free copper	Composilex 2	DNA Quad Helix	silver-clad OFC		130	180	230	
EQUINOX 7 SUBWOOFER CABLE (ESM) 			OCC copper	Composilex 2	DNA Quad Helix	silver-clad OFC		310	450	590	
TONEARM CABLES (Female tonearm DIN plug to 2 RCA or 2 XLR males)			1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)	HEADPHONE CABLES (Connectors must be specified for both ends)			1.5m (5 ft.)	2.0m (6.5 ft.)	3.0m (10 ft.)
SOLSTICE 7 (SOT) 			240	260	280	ECLIPSE 7 (ECH) 			475	500	550
ECLIPSE 7 (ECT) 			400	450	500	SILVER ECLIPSE 7 (SEH) 			600	650	750
SILVER ECLIPSE 7 (SET) 			500	600	700	PLATINUM ECLIPSE 7 (PEH) 			1,260	1,480	1,920
PLATINUM ECLIPSE 7 (PET)			1,380	1,820	2,260						

SPEAKER CABLE - STANDARD PAIRS (All UL-CL3/CSA-FT4 except Horizon)	\$ / foot \$/ meter	Conductor, AWG / mm ²	Cable design	Contact materials	STANDARD PAIRS (spades are standard, bananas optional)				
					2.0m (6.5 ft.)	2.5m (8 ft.)	3.0m (10 ft.)	5.0m (16.4 ft.)	6.0m (20 ft.)
HORIZON™ (HOS) 	1.20/ft. 4/m	OFC 16ga./1.25mm ²	Flexi-Flat™	gold / silver / OFC	66	70	74	90	98
STREAM™ 7 (STS) 	1.80/ft. 6/m	OFC 16ga./1.25mm ²	DNA Dual Helix®	gold / silver / OFC	84	90	96	120	132
LUNA™ 7 (LUS) 	3/ft. 10/m	OFC 14ga./2mm ²	DNA Quad Helix®	gold / silver / OFC	110	120	130	170	190
SOLSTICE® 7 (SOS) 	4.50/ft. 15/m	OFC 13ga./2.5mm ²	DNA Quad Helix	gold / silver / OFC	140	155	170	230	260
OASIS® 7 (OAS) 	12/ft. 40/m	OFC 12ga./3.6mm ²	DNA Quad Helix	silver-clad OFC	310	350	390	550	630
EQUINOX® 7 (EQS) 	36/ft. 120/m	OCC copper 12ga./3.6mm ²	DNA Quad Helix	silver-clad OFC	630	750	870	1,350	1,590
MINI ECLIPSE™ 7 (MES) 	21/ft. 70/m	OCC copper 14ga./2mm ²	DNA Quad Helix	silver-clad OFC	430	500	570	850	990
ECLIPSE™ 7 (ECS) 	75/ft. 250/m	OCC copper 10ga./4.8mm ²	DNA Octo Helix®	silver-clad OFC	1,300	1,550	1,800	2,800	3,300
SILVER ECLIPSE™ 7 (SES) 	180/ft. 600/m	OCC silver-clad copper 10ga./4.8mm ²	DNA Octo Helix	silver-clad OFC	2,700	3,300	3,900	6,300	7,500
GOLD ECLIPSE™ 7 (GES) 	600/ft. 2,000/m	solid silver 11ga./4mm ²	DNA Octo Helix	silver-clad OFC	8,300	10,300	12,300	20,300	24,300
PLATINUM ECLIPSE™ 7 (PES) 	1,200/ft. 4,000/m	OCC solid silver 9ga./6mm ²	DNA Octo Helix	silver-clad OFC	16,400	20,400	24,400	40,400	48,400
SPEAKER CABLE - BIWIRED PAIRS (All UL-CL3/CSA-FT4)	\$ / foot \$/ meter	Conductor, AWG / mm ²	Cable design	Contact materials	BIWIRED PAIRS (spades are standard, bananas optional)				
					2.0m (6.5 ft.)	2.5m (8 ft.)	3.0m (10 ft.)	5.0m (16.4 ft.)	6.0m (20 ft.)
LUNA 7 (LUB) 	3/ft. 10/m	OFC 14ga./2mm ²	DNA Quad Helix	gold / silver / OFC	140	150	160	200	220
SOLSTICE 7 (SOB) 	4.50/ft. 15/m	OFC 13ga./2.5mm ²	DNA Quad Helix	gold / silver / OFC	180	195	210	270	300
OASIS 7 (OAB) 	12/ft. 40/m	OFC 12ga./3.6mm ²	DNA Quad Helix	silver-clad OFC	360	400	440	600	680
EQUINOX 7 (EQB) 	36/ft. 120/m	OCC copper 12ga./3.6mm ²	DNA Quad Helix	silver-clad OFC	680	800	920	1,400	1,640
MINI ECLIPSE 7 (MEB) 	21/ft. 70/m	OCC copper 14ga./2mm ²	DNA Quad Helix	silver-clad OFC	480	550	620	900	1,040
ECLIPSE 7 (ECB) 	75/ft. 250/m	OCC copper 10ga./4.8mm ²	DNA Octo Helix	silver-clad OFC	1,400	1,650	1,900	2,900	3,400
SILVER ECLIPSE 7 (SEB) 	180/ft. 600/ZZ	OCC silver-clad copper 10ga./4.8mm ²	DNA Octo Helix	silver-clad OFC	2,800	3,400	4,000	6,400	7,600
GOLD ECLIPSE 7 (GEB) 	600/ft. 2,000/M	solid silver 11ga./4mm ²	DNA Octo Helix	silver-clad OFC	8,400	10,400	12,400	20,400	24,400
PLATINUM ECLIPSE 7 (PEB) 	1,200/ft. 4,000/M	OCC solid silver 9ga./6mm ²	DNA Octo Helix	silver-clad OFC	16,500	20,500	24,500	40,500	48,500

POWER CONDITIONING CORDS – Ultra-quiet and dynamic. Flexible flat design bends and coils easily. Longer lengths are more effective.		Conductor material	Insulation material	Cable design	Plug contact material	1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)	3.0m (10 ft.)			
STRATUS™ 7 Power Cord (STP)		oxygen-free copper	Composilex® 2	Fluxfield™	silver-clad copper alloy	90	105	120	150			
AURORA™ 7 Power Cord (AUP)		silver-clad OFC	Composilex 2	Fluxfield	silver-clad copper alloy	140	170	200	260			
ELECTRA™ 7 Power Cord (ELP)		OCC copper	Composilex 2	Fluxfield	silver-clad copper alloy	240	300	360	480			
SILVER ELECTRA™ 7 Power Cord (SEP)		OCC silver-clad copper	Composilex 2	Fluxfield	silver-clad copper alloy	450	575	700	950			
PLATINUM ELECTRA™ Power Cord (PEP)		OCC solid silver	Composilex 2	Fluxfield	OCC silver-clad copper	1,700	2,350	3,000	4,300			
POWER CORD CONNECTOR UPGRADE – Standard & custom lengths				POWER CORD ADAPTERS								
- Silver-clad copper alloy contacts - Flat clamp for STP / AUP / ELP / SEP only - Standard lengths may be upgraded with this connector - All custom length cords and standard length upgraded cords will be priced according to the custom pricing chart below												
				GNDLIFT 6	IECMFG8 17	IECM1F 17	IECM2F 20					
POWER STRIP												
MATRIX 2	OFC star-wired, rack mountable shielded power cord extender								120			
COAXIAL DIGITAL CABLES (75 ohms, RCA plugs, BNC's optional)	Conductor material	Insulation material	Cable design	Plug Contact materials	0.5m (20 in.)	1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)	3.0m (10 ft.)	6.0m (20 ft.)		
CHROMA™ (CRV)		oxygen-free copper	foamed PE	coaxial	gold / silver / OFC	18	20	22	24	28	40	
ULTRAVIOLET™ (UVV)		silver-plated OFC	foamed PE	coaxial	gold / silver / OFC	31	35	39	43	51	75	
STARLIGHT 7 (STV)		silver-clad OCC & OFC	Composilex 2	DNA Helix	silver-clad OFC	60	80	100	120	160	280	
SILVER STARLIGHT® 7 (SSV)		OCC silver-clad copper	Composilex 2	DNA Helix	silver-clad OFC	200	250	300	350	450	750	
GOLD STARLIGHT 7 (GSV)		OCC solid silver	Composilex 2	DNA Helix	silver-clad OFC	325	500	675	850	1,200	2,250	
PLATINUM STARLIGHT (PSV)		OCC solid silver	Composilex	DNA Helix	silver-clad OFC	850	1,500	2,150	2,800	4,100	8,000	
BALANCED DIGITAL AUDIO CABLES (110-ohm XLR female to XLR male)		Conductor material	Insulation material	Cable design	Plug contact materials	0.5m (20 in.)	1.0m (40 in.)	1.5m (5 ft.)	2.0m (6.5 ft.)	3.0m (10 ft.)	6.0m (20 ft.)	
LUNA™ 7 (LUA)			oxygen-free copper	Composilex 2	DNA Helix®	silver-clad copper alloy	49	53	57	61	69	93
STARLIGHT® (STA)			OCC silver-clad copper	Composilex	DNA Helix	silver-clad copper alloy	80	115	150	185	255	465
GOLD STARLIGHT® 7 (GSA)			OCC solid silver	Composilex 2	DNA Helix	silver-clad copper alloy	325	500	675	850	1,200	2,250
PLATINUM STARLIGHT® (PSA)			OCC solid silver	Composilex 2	DNA Helix	silver-clad copper alloy	850	1,500	2,150	2,800	4,100	8,000
TOSLINK OPTICAL - DIGITAL AUDIO			Conductor material	0.3m (1 ft.)	0.5m (20 in.)	1.0m (40 in.)	2.0m (6.5 ft.)	3.0m (10 ft.)	5.0m (16.4 ft.)			
NOVA™ Toslink Optical (NTO)				PMMA monofilament	n/a	35	40	50	60	70		
NOVA Toslink to 3.5mm Connector (NMO)				PMMA monofilament	n/a	35	40	50	60	70		

Because we are continually striving to improve our products, all specifications and prices are subject to change without notice.

Wireworld, Inc. • 6545 Nova Drive • Suite 204 • Davie • Florida 33317 USA • Tel. 954.474.4464 • Fax 954.474.4414

e-mail: sales@wireworldcable.com • www.wireworldcable.com